

Foot Switches SFS-UFS Accessories

AC-K1T20

Kit for joining two footswitches together
Polymer thermoplastic

AC-K1T22

Carrying rod L=600mm
For use with **AC-K1T20**

AC-K1T29

Aluminium rod Ø=25mm, L=740mm with M25x1.5 threaded ends
For use with **AC-K1T33** supplied with brass nuts & gaskets

AC-K1T30

Kit for joining two footswitches together
Polymer thermoplastic. For use with **AC-K1T29**

AC-K1T33

Emergency Stop station 1NC+1NO
For use with **AC-K1T29**

AC-K1T40

Double carrying rod L=400mm
For use with three foot switches joined together by two **AC-K1T20**

AC-K1T61

Stabilising plate for two joined foot switches
For use with **SFS/UFS** foot switches

AC-K1T71

Metal shroud
For use with **UFS** foot switches



Contact Blocks

Housing Material: Glass reinforced polymer self-extinguishing shock proof thermoplastic

Electrical Data				
Thermal current (I _{th})	10A			
Rated insulation voltage (U _i)	500VAC 600VDC			
Utilisation Categories		Alternating current: AC15 (50/60Hz)		
Voltage V		250	400	500
Current A		6	4	1
Direct current: DC13				
Voltage V		24	125	250
Current A		6	1.1	0.4

AC-C501

1NO+1NC Snap action
for use with SFS/UFS foot switch

AC-C501-G

1NO+1NC Snap action (gold plated contact)
for use with SFS/UFS foot switch

AC-C601

1NO+1NC Slow action
for use with SFS/UFS foot switch

AC-C1001

2NO Slow action

AC-C1501

2NO Slow action shifted

